

GENERAL NOTES:

- 1. Engineer may reduce the advisory speed if deemed appropriate.
- 2. Speed Limit refers to the legally established speed limit before construction and not the advisory speed during construction.
- 3. Contractor shall be responsible for placement and removal of white edge lines, yellow "No Passing" lines and 24-inch wide stop lines, Dashed yellow centerline or yellow "No Passing" line between the stop lines shall be removed prior to the beginning of construction and replaced before opening to two-way traffic. Reflectors shall be removed before opening to two-way
- 4. Signal timing shall be set as approved by the Engineer.
- 5. For temporary floodlighting, see Detail Sheet 570-2.
- 6. Pole for temporary floodlighting and span wire, and poles used to furnish power to signals or floodlights shall be offset 30 feet from the traveled way unless there are right-of-way restrictions. Clearance on overhead wiring for signals and floodlighting shall be a minimum of 18 feet.

- 7. Left signal head to be centered over traffic lane.
- 8. This layout is not appropriate when ADT (Average Daily Traffic) exceeds
- 9. Details for the Temporary Barrier Rail are included elsewhere in the plans.
- 10. Reflectors shall be mounted back-to-back on each section of Temporary Barrier Rail. Reflectors shall face oncoming traffic as indicated.
- 11. Signals shall rest in RED.
- 12. The traffic actuated controller shall comply with the latest NEMA and ITE standards for actuated signals.
- 13. A detection area shall be located near the stop line with the downstream edge positioned 6' from the stop line. A second detection area shall be located 100 to 150 feet in advance of the stop line. The size of the detection areas shall be approximately 6' x 10'. A single above-ground detector may be used to provide detection for both areas.



lowa Department of Transportation Highway Division

STANDARD ROAD PLAN

REVISION: Revise note 13.	REVISION NO.
	7
William Q. Steen	REVISION DATE
	04.00.00
APPROVED BY DESIGN METHODS ENGINEER	04-30-02

TRAFFIC CONTROL LAYOUT ONE-WAY TRAFFIC ON BRIDGES FOR 8-FOOT APPROACH SHOULDERS

LEGEND

Traffic Sign

Temporary Floodlighting



Type "B" High Intensity Flashing Warning Light



Work and Storage Area

 \leftarrow Traffic Signal